# **Cat<sup>®</sup> Compactor Oil**



## **Exceptional Rust and Corrosion Protection**

Cat<sup>®</sup> Compactor Oil Synthetic Oil is a premium PAO (Polyalpaolefin) synthetic gear and a bearing lubricant with no viscosity improvers. Cat Compactor Oil is the only oil recommended by Caterpillar for use in certain compartments of Cat Compactors and Cat Hydraulic Mining Shovels.

### **Applications**

- All 500 Series soil compactors with the new pod style drum
- All earlier model 500 series compactors without oil pockets in the old style drum
- Distribution gearboxes, travel gearboxes, and swing gearboxes in Cat Hydraulic Mining Shovels





## **Cat® Compactor Oil**

| Typical Characteristics*  |           |  |  |  |
|---|-----------|--|--|--|
| ISO Viscosity Grade   | 220       |  |  |  |
| Specific Gravity  | .87       |  |  |  |
| Gravity, API  | 31.1      |  |  |  |
| Pour Point, °C (°F) min, ASTM D97   | -42 (-44) |  |  |  |
| Flash Point, °C (°F) min, ASTM D92  | 240 (464) |  |  |  |
| Viscosity   |           |  |  |  |
| cSt @ 40°C (ASTM D445)  | 221       |  |  |  |
| cSt @ 100°C (ASTM D445)   | 28.5      |  |  |  |
| Viscosity Index (ASTM D2270)  | 169       |  |  |  |
| Copper Corrosion (ASTM D130 24 hrs at 121°C)                                | 1B        |  |  |  |
| Rust Protection (ASTM D665A and D665B,<br>Distilled and Synthetic sea water | Pass      |  |  |  |
| FZG Scuffing, Fail Stage, DIN 51534   | 13+       |  |  |  |
| TOST Life, Hours, ASTM D943-2   | 10,000+   |  |  |  |

\* The values shown are typical values and should not be used as quality control parameters to either accept or reject product. Specifications are subject to change without notice.

| Package Size |          |        |          |  |
|--------------|----------|--------|----------|--|
| Gallons      |          | Liters |          |  |
| 1            | 353-4980 |        |          |  |
| 5            | 4C-6767  | 20     | 456-5476 |  |
| 55           | 417-9262 | 208    | 456-5477 |  |

#### Benefits

- High anti-wear properties reduce component wear and extends working life
- Superior rust and corrosion protection
- Minimizes effects of micro slip in rolling contact bearings for longer rolling-element life potential
- Extends equipment high temperature operating capability

# S•O•S<sup>™</sup> Services for early problem detection

Protect your investment with Cat S•O•S oil analysis, the ultimate detection and diagnostic tool for your equipment. S•O•S helps you detect potential problems before they can lead to major failures and costly, unscheduled downtime.

# Cat<sup>®</sup> Filters: Complete protection for your machine

Combine Cat Fluids with Cat Filters for the highest level of contamination control and protection for your machine. We recommend Cat Filters for all Cat machine application.

#### CAT DEALERS DEFINE WORLD-CLASS PRODUCT SUPPORT.

We offer you the right parts and service solutions, when and where you need them.

The Cat Dealer network of highly trained experts are built to help you maximize your equipment investment.

## **BUILT FOR IT.**

PEHJ0437 www.cat.com

© 2014 Caterpillar • All Rights Reserved • Printed in USA CAT, CATERPILLAR, BUILT FOR IT, their respective logos, "Caterpillar Yellow", the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.



